

Retrofit spring-return actuator for fire and smoke dampers 90° in ventilation and air-conditioning systems

- Nominal torque 15 Nm / 15 Nm
- Nominal voltage AC 230 V
- Control open-close
- Spindle drive clamp 3/4"


Technical data

Electrical data	Nominal voltage	AC 230 V
	Nominal voltage frequency	50/60 Hz
	Nominal voltage range	AC 198 V ... 262 V
	Power consumption in operation	11 W
	Power consumption at rest	3.5 W
	Power consumption for wire sizing	12 VA
	Power consumption for wire sizing note	I _{max} 0.5 A @ 5 ms
	Auxiliary switch	2 x SPDT
	Switching capacity auxiliary switch	Contact gold-plated silver: 1 mA ... 6 (3) A, DC 5 V ... AC 250 V (II Totally insulated)
	Switching points auxiliary switch	<10° (fix) / >30° ... 90° (adjustable)
Connection supply	Cable 1 m, 2 x 0.75 mm ² (halogen-free)	
Connection auxiliary switch	Cable 1 m, 6 x 0.75 mm ² (halogen-free)	
Functional data	Torque motor	Min. 15 Nm
	Torque spring-return	Min. 15 Nm
	Direction of rotation motor	Can be selected by mounting L / R
	Angle of Rotation	Max. 95° (incl. 5° initial spring tension)
	Running time motor	<75 s
	Running time spring-return	<20 s
	Sound power level motor max.	45 dB (A)
	Sound power level spring-return max.	63 dB (A)
	Position indication	Mechanical, with clamp
	Service life	Min. 20,000 safety positions
Safety	Protection class IEC/EN	II Totally insulated
	Degree of protection IEC/EN	IP54 in all mounting positions
	EMC	CE according to 2014/30/EU
	Low-voltage directive	CE according to 2014/35/EU
	Certification IEC/EN	Certified according to IEC/EN 60730-1 and IEC/EN 60730-2-14
	Mode of operation	Type 1.AA.B
	Rated impulse voltage supply / control	4 kV
	Control pollution degree	3
	Ambient temperature normal duty	-30°C ... 50°C
	Ambient temperature safety duty	The safety position will be attained up to max. 75°C when triggered by a thermal fuse
Non-operating temperature	-40°C ... 80°C	
Ambient humidity	95% r.h., non-condensing	
Maintenance	Maintenance-free	
Weight	Weight approx.	3.1 kg

Safety notes



- The device must not be used outside the specified field of application, especially not in aircraft or in any other airborne means of transport.
- Caution: Power supply voltage!
- The actuator is adapted and mounted to the fire and smoke damper by the damper manufacturer. For this reason, the actuator is only supplied direct to safety damper manufacturers. The manufacturer then bears full responsibility for the proper functioning of the damper.
- The device may only be opened at the manufacturer's site. It does not contain any parts that can be replaced or repaired by the user.
- The device contains electrical and electronic components and must not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

Product features

Mode of operation	The actuator moves the damper to the operating position at the same time as tensioning the return spring. The damper is turned back to the safety position by spring energy when the supply voltage is interrupted.
Signalling	Two microswitches with fixed settings are installed in the actuator for indicating the damper end positions. The position of the damper blade can be read off on a mechanical position indicator.
Manual operation	Without power supply, the damper can be operated manually and fixed in any required position. It can be unlocked manually or automatically by applying the supply voltage.
Standards / Regulations	The design of the actuator is based on the specific requirements from the European standards: - EN 15650 Ventilation for buildings – Fire dampers - EN 1366-2 Fire resistance tests on service installations (Part 2: Fire dampers) - EN 13501-3 Fire classification of construction products and building elements (Part 3: Classification using data from fire resistance tests on products and elements used in building service installations: fire resisting ducts and fire dampers)
Recommendation for application	Regular operational checks (open-close control of the fire damper) enhance the safety of people, animals, property and the environment. Unless other requirements are stipulated – e. g. in the damper manufacturer's operating instructions – Belimo recommends the performance of monthly operational checks. Fire damper actuators from Belimo are designed in accordance with service life specifications contained in the technical data sheet for regular operational checks. Notes for regular operational checks can be found in the European Product Standard for Fire Dampers (EN 15650) under «Maintenance information».


Electrical installation



- Notes**
- Caution: Power supply voltage!
 - Parallel connection of other actuators possible. Note the performance data.

Wiring diagrams

AC 230 V, open-close



Cable colours:

- 1 = blue
- 2 = brown

- S1 = white
- S2 = white
- S3 = white
- S4 = white
- S5 = white
- S6 = white

Dimensions [mm]

Dimensional drawings

3/4"-spindle clamp (with insertion part)

Damper spindle	Length		
	≥85	10...20	10...16
	≥15		

